

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/058590 A1

(51) International Patent Classification⁷: B30B 15/06, 1/32

(21) International Application Number:
PCT/SE2004/001855

(22) International Filing Date:
14 December 2004 (14.12.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0303402-2 17 December 2003 (17.12.2003) SE

(71) Applicant (for all designated States except US): AU-
TOMATION PRESSES TOOLING AP & T AB
[SE/SE]; Industrigatan 5, S-514 32 Tranemo (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KARLSSON,

Mikael [SE/SE]; Andra Guldv. 1, S-514 31 Tranemo
(SE). WALKIN, Bengt [SE/SE]; Trestegsv. 7, S-514 31
Tranemo (SE).


(74) Agents: WALLENGREN, Yngvar et al.; Patentbyrå Y
Wallengren AB, Box 116, S-331 21 Värnamo (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR COMPENSATING FOR STRESS DEFORMATIONS IN A PRESS



(57) Abstract: The disclosure relates to an apparatus for compensating for such deformations as occur in operation in first and second clamping surfaces (52, 53) intended for a tool (9) in a press (1), the clamping surfaces being reciprocally moveable towards and away from one another in order to move a first and second part of the tool (9) towards and away from one another, and the first and second tool parts have a first and second abutment surface (54, 55, respectively) for abutment against the first and second clamping surface (52, 53, respectively) and the deformations cause uneven pressure in at least on contact region (56) between the tool (9) and the clamping surfaces (52, 53). According to the present invention, there is disposed, in at least one contact region (56) between a clamping surface (52) and an abutment surface (54), a power unit which, on activation, is operative to press, away from the clamping surface (52) located in the contact region (56) at least a part of the abutment surface (54) of the tool (9) located there.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report